

# METAL HALIDE GLOBES

- 302. SINGLE ENDED MH GLOBES***
- 302. DOUBLE ENDED MH GLOBES***
- 303. PAR MH GLOBES***
- 304. ARC MH GLOBES***

# SINGLE ENDED METAL HALIDE GLOBES

**PRODUCT FEATURES**

- Input voltage: 240V AC with control gear
- Wattage: 35W, 70W & 150W
- Reduced UV output
- Excellent colour rendering
- High intensity light output
- Not suitable for dimming

**WARRANTY**

- 1 year replacement warranty



**10,000  
HRS**

**GROUP: GLMETH**

CODE	DESCRIPTION	BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMM	DIAM (mm)	LENGTH (mm)	CARTON QTY
CLAMHS35W4000K	35W G12 SINGLE ENDED MH 4000K	G12	4000	2450	35	-	NO		95	1/12
CLAMHS35W5000K	35W G12 SINGLE ENDED MH 5000K	G12	5000	2450	35	-	NO		95	1/12
CLAMHS70W3000K	70W G12 SINGLE ENDED MH 3000K	G12	3000	4550	70	-	NO		95	1/12
CLAMHS70W4000K	70W G12 SINGLE ENDED MH 4000K	G12	4000	4550	70	-	NO		95	1/12
CLAMHS70W5000K	70W G12 SINGLE ENDED MH 5000K	G12	5000	4550	70	-	NO		95	1/12
CLAMHS150W3000K	150W G12 SINGLE ENDED MH 3000K	G12	3000	10500	150	-	NO		95	1/12
CLAMHS150W4000K	150W G12 SINGLE ENDED MH 4000K	G12	4000	10500	150	-	NO		95	1/12
CLAMHS150W5000K	150W G12 SINGLE ENDED MH 5000K	G12	5000	10500	150	-	NO		95	1/12

# DOUBLE ENDED METAL HALIDE GLOBES

**PRODUCT FEATURES**

- Input voltage: 240V AC with control gear
- Wattage: 35W, 70W & 150W
- Reduced UV output
- Excellent colour rendering
- High intensity light output
- Not suitable for dimming

**WARRANTY**

- 1 year replacement warranty



10,000  
HRS

GROUP: GLMETH

CODE	DESCRIPTION	BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMM	DIAM (mm)	LENGTH (mm)	CARTON QTY
CLAMHD35W3000K	35W RX7S DOUBLE ENDED MH 3000K	RX7S	3000	2800	35	-	NO		114	1/12
CLAMHD35W4000K	35W RX7S DOUBLE ENDED MH 4000K	RX7S	4000	2800	35	-	NO		114	1/12
CLAMHD35W5000K	35W RX7S DOUBLE ENDED MH 5000K	RX7S	5000	2800	35	-	NO		114	1/12
CLAMHD70W4000K	70W RX7S DOUBLE ENDED MH 4000K	RX7S	4000	4900	70	-	NO		114	1/12
CLAMHD150W3000K	150W RX7S DOUBLE ENDED MH 3000K	RX7S	3000	11250	150	-	NO		132	1/12

## PAR CERAMIC METAL HALIDE GLOBES

### PRODUCT FEATURES

- Input voltage: 240V AC with control gear
- Wattage: 35W & 70W
- Higher performance than standard metal halide
- Lumen output 85-110 lumen/watt
- Reduced UV output
- Excellent colour rendering 85-95
- High intensity light output
- Not suitable for dimming

### WARRANTY

- 1 year replacement warranty



10,000  
HRS

GROUP: GLMETH

CODE	DESCRIPTION	BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMM	DIAM (mm)	LENGTH (mm)	CARTON QTY
CLAMCP2035W10D3K	35W CERAMIC PAR20 10DEG E27 MH	E27	3000	1722	35	-	NO	Ø64	95	1/24
CLAMCP2035W30D3K	35W CERAMIC PAR20 30DEG E27 MH	E27	3000	1722	35	-	NO	Ø64	95	1/24
CLAMCP3035W10D3K	35W CERAMIC PAR30 10DEG E27 MH	E27	3000	1700	35	-	NO	Ø95	122	1/24
CLAMCP3070W10D3K	70W CERAMIC PAR30 10DEG E27 MH	E27	3000	4122	70	-	NO	Ø95	122	1/24
CLAMCP3070W40D3K	70W CERAMIC PAR30 40DEG E27 MH	E27	3000	4122	70	-	NO	Ø95	122	1/24

# ARC CERAMIC METAL HALIDE GLOBES

**PRODUCT FEATURES**

- Input voltage: 240V AC with control gear
- Wattage: 70W & 150W
- Higher performance than standard metal halide
- Lumen output 85-110 lumen/watt
- Reduced UV output
- Excellent colour rendering 85-95
- High intensity light output
- Not suitable for dimming

**WARRANTY**

- 1 year replacement warranty

**12,000  
HRS**



**GROUP: GLMETH**

CODE	DESCRIPTION	BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMM	DIAM (mm)	LENGTH (mm)	CARTON QTY
CLAMCD70W3K	70W CERAMIC RX7S MH 3000K	RX7S	3000	5265	70	-	NO	Ø19	119	1/12
CLAMCD70D4K	70W CERAMIC RX7S MH 4000K	RX7S	4000	4900	70	-	NO	Ø19	119	1/12
CLAMCD150W3K	150W CERAMIC RX7S MH 3000K	RX7S	3000	10800	150	-	NO	Ø22	138	1/12
CLAMCD150W4K	150W CERAMIC RX7S MH 4000K	RX7S	4000	11400	150	-	NO	Ø22	138	1/12

**PRODUCT FEATURES**

- Input voltage: 240V AC with control gear
- Wattage: 70W & 150W
- Higher performance than standard metal halide
- Lumen output 85-110 lumen/watt
- Reduced UV output
- Excellent colour rendering 85-95
- High intensity light output
- Not suitable for dimming

**WARRANTY**

- 1 year replacement warranty

**12,000  
HRS**



**GROUP: GLMETH**

CODE	DESCRIPTION	BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMM	DIAM (mm)	LENGTH (mm)	CARTON QTY
CLAMCG1270W3K	70W CERAMIC SINGLE ENDED G12 MH 3K	G12	3000	5600	70	-	NO	Ø19	100	1/12
CLAMCG12150W3K	150W CERAMIC SINGLE ENDED G12 MH 3K	G12	3000	11200	150	-	NO	Ø22	110	1/12
CLAMCG12150W4K	150W CERAMIC SINGLE ENDED G12 MH 4K	G12	3000	10400	150	-	NO	Ø22	110	1/12

## PRODUCT FEATURES

- Input voltage: 240V AC with control gear
- Wattage: 35W
- Higher performance than standard metal halide
- Lumen output 85-110 lumen/watt
- Reduced UV output
- Excellent colour rendering 85-95
- High intensity light output
- Not suitable for dimming

## WARRANTY

- 1 year replacement warranty

**12,000  
HRS**



## GROUP: GLMETH

CODE	DESCRIPTION	BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMM	DIAM (mm)	LENGTH (mm)	CARTON QTY
<b>CLAMCG835W3K</b>	35W CERAMIC SINGLE ENDED MH G8.5 3K	G8.5	3000	2650	35	-	NO	Ø14	95	1/12
<b>CLAMCG835W4K</b>	35W CERAMIC SINGLE ENDED MH G8.5 4K	G8.5	4000	2650	35	-	NO	Ø14	95	1/12