

EXELITE & SJS PRODUCTS

328. SMART STARTER CHARGERS

332. LED HAND TORCHES

333. LED HEAD LIGHTS

334. LED MERCHANDISER

334. LED WORK LIGHTS & TORCHES

335. LED WORK LIGHTS

SMART START CHARGERS



SJS01G2

12V 400AMP Jump Start most vehicles up to 4000cc petrol only. Not recommended for V-TWIN Motorcycles over 1000cc

- **Power pack:** 134mm x 77.5mm x 32.6mm, weight: 275g
- **Jump start output:** 12V DC, 400Amp peak / 200Amp start
- **Jumper leads:** Jump Start Safe Technology & AWG cable with MOSFET. Reverse current: >2Amp max. 18V DC Max. Voltage difference, recognition, short circuit protection
- **Safety protection:** Over-discharge, overcharge, resettable overload, digital charging voltage and current protection, enclosed jump port terminals
- **Battery chargers:** SAA approved 240V AC/15V DC, 1A wall charger. 12V/15V DC 800mA car charger
- **Ambient temp:** -20 to 60°C
- **Self discharge:** 10 to 15% over 12 months from full charge (with power switch in 'OFF' position)
- **Device charging:** USB port 5V DC, 2.1A with 4 in 1 USB cable IS8 compliant. Multi volt port 12V, 16V, 19V DC cable + 8 adaptors
- **LED flashlight:** 3 modes: full on, SOS, emergency flash
- **Packing:** Zip carry bag, 10pcs per outer carton
- **Warranty:** 1 year replacement warranty



SJS05G2

12V 500AMP Jump Start most vehicles up to 3000cc diesel & 6000cc petrol

- **Power pack:** 165mm x 79mm x 40mm, weight: 495g power pack only
- **Jump start output:** 12V DC, 500Amp peak / 300Amp start
- **Jumper leads:** Jump Start Safe Technology & AWG cable with MOSFET. Reverse current: >2Amp max. 18V DC Max. Voltage difference, recognition, short circuit, Reverse Polarity, Overheat temp sensor, Power pack low voltage, Anti Surge
- **Safety protection:** Over-discharge, overcharge, resettable overload, digital charging voltage and current recognition, enclosed jump port terminals
- **Battery chargers:** SAA approved 240V AC/15V DC, 1Amp, 12V/15V DC 800mA car charger
- **Ambient temp:** -20 to 60°C
- **Charge Cycles:** up to 2,000
- **Self discharge:** 10 to 15% over 12 months from full charge with switch
- **Device charging:** USB port 5V DC, 2.1A with 4 in 1 USB cable IS8 compliant. Multi volt port 12V, 16V, 19V DC cable + 8 adaptors
- **LED flashlight:** 3 modes: full on, SOS, emergency flash
- **Warranty:** 1 year replacement warranty



SJS06G2

12V 600AMP Jump Start most vehicles up to 4500cc diesel & 7000cc petrol

- **Power pack:** 186mm x 85mm x 43mm, weight: 540g power pack only
- **Jump start output:** 12V DC, 600Amp peak / 300Amp start
- **Jumper leads:** Jump Start Safe Technology & AWG cable with MOSFET. Reverse current: >2Amp max. 18V DC Max. Voltage difference, recognition, short circuit, Reverse Polarity, Overheat temp sensor, Power pack low voltage, Anti Surge
- **Safety protection:** Over-discharge, overcharge, resettable overload, digital charging voltage and current recognition, enclosed jump port terminals
- **Battery chargers:** SAA approved 240V AC/15V DC, 1Amp, 12V/15V DC 800mA car charger
- **Ambient temp:** -20 to 60°C
- **Charge Cycles:** up to 2,000
- **Self discharge:** 10 to 15% over 12 months from full charge with switch
- **Device charging:** USB port 5V DC, 2.1A with 4 in 1 USB cable IS8 compliant. Multi volt port 12V, 16V, 19V DC cable + 8 adaptors
- **LED flashlight:** 3 modes: full on, SOS, emergency flash
- **Warranty:** 1 year replacement warranty

SJS06G2TP

12V 600AMP Jump Start most vehicles up to 4500cc diesel & 7000cc petrol (TP001 0-80psi tyre pump included)

- **Power pack:** 186mm x 85mm x 43mm, weight: 540g power pack only
- **Jump start output:** 12V DC, 600Amp peak / 300Amp start
- **Jumper leads:** Jump Start Safe Technology & AWG cable with MOSFET. Reverse current: >2Amp max. 18V DC Max. Voltage difference, recognition, short circuit, Reverse Polarity, Overheat temp sensor, Power pack low voltage, Anti Surge
- **Safety protection:** Over-discharge, overcharge, resettable overload, digital charging voltage and current recognition, enclosed jump port terminals
- **Battery chargers:** SAA approved 240V AC/15V DC, 1Amp, 12V/15V DC 800mA car charger
- **Ambient temp:** -20 to 60°C
- **Charge Cycles:** up to 2,000
- **Self discharge:** 10 to 15% over 12 months from full charge with switch
- **Device charging:** USB port 5V DC, 2.1A with 4 in 1 USB cable IS8 compliant. Multi volt port 12V, 16V, 19V DC cable + 8 adaptors
- **LED flashlight:** 3 modes: full on, SOS, emergency flash
- **Tyre Pump:** 0-80psi 2.5 to 6Amp Current Draw (205/65R15 to 40psi 15 min)
- **Warranty:** 1 year replacement warranty



TP001

For use with Generation 1 Smart Start Charger: SSC01, SSC05, SSC06 & Generation 2 Smart Start Charger: SJS01G2, SJS05G2, SJS06G2

- Inflates 205/65R15 tyre to 40psi in 15 min
- Quality screw on valve fitting
- Zip carry bag
- 2x ball and camping adaptors
- LED Light and ON/OFF switch
- 110mm hose, 500mm cable
- 12V DC input
- Dimensions: 105mm x 95mm x 45mm
- Current draw: 2.5A to 6A
- **Warranty:** 1 year replacement warranty



JSSJL156

Jump leads to suit Generation 2 SJS05G2, SJS06G2, SJS06G2TP, retrofit upgrade for SSC01, SSC05, SSC06, SSC06TP

- **Standby:** solid red LED
Jumper leads connected to Power Pack and in SHORT CIRCUIT protection mode
- **Battery Detection:** solid red LED
Jumper clamps connected to battery but vehicle battery has less than 6V. (no output) recharge/replace vehicle battery
- **Correct Connection:** solid red LED
Jumper clamps are connected correctly to the vehicle battery terminals. Ready to jump start (1 min time out)
- **Incorrect Connection:** fast red flash LED
Jumper leads are not connected to the vehicle battery terminals correctly (No output)
- **Over Temperature:** slow green flash LED
Jumper leads are over heating from continuous cranking or overload. (No output) until leads cool down
- **Low voltage:** fast green flash LED
Power pack voltage is too low for jump starting attempt. Fully charge the power pack. (No output)
- **Voltage differential:** alternate red/green flash LED
Vehicle battery voltage is higher than power pack. (No output)
- **Reverse current:** alternate red/green flash LED
Vehicle engine has started and is running. (No output) Disconnect power pack from vehicle battery immediately

SPECIFICATIONS

- Cable: 8AWG 200°C
- Clamps: insulated copper
- Forward Current: 800A max.
- Reverse Current: 2A max. 18V Max.
- Battery Detection: Min.6V
- Overheat Cut-out: 60°C
- Cool down: Approx. 3min
- Reset: Manual button
- Time out: 1min to Red flashing LED

WARRANTY

- 1 year replacement warranty



LED HAND TORCHES



LED10FOXTCH

- LED 780 lumens brightness with 200m range
- Wattage: 10W
- 1x18650 Li-ion rechargeable battery
- Product size: 124.5 x 26.5 x 26.5mm
- 95g excluding battery
- Aeronautical aluminium alloy
- IP rating: IP65 waterproof
- Battery running time up to 1.5 hours
- 1 year replacement warranty



AERONAUTICAL ALUMINIUM ALLOY

LED10COUGARTCH

- LED 780 lumens brightness with 500m range
- Wattage: 10W
- 1x18650 Li-ion rechargeable battery
- Product size: 186 x 48 x 27mm
- 195g excluding battery
- Aeronautical aluminium alloy
- IP rating: IP65 waterproof
- Battery running time up to 1.5 hours
- 1 year replacement warranty



AERONAUTICAL ALUMINIUM ALLOY

CHIEF

- CREE XM-L2 series LED chips
- Wattage: 10W
- Rechargeable 18650 Li-ion batteries
- Length: 170mm, Diam: 58mm
- Weight: 398g (battery excluded)
- Aeronautical aluminium alloy
- IP rating: IP65 waterproof
- Light distance: 5m
- Adjustable beam: 4 x Zoom by rotating lens
- 3 year replacement warranty



LED HEAD LIGHT



LED3HPL

This head light is mainly used for camping and outdoor sports such as fishing, hunting and running

- Wattage: 3W, Brightness: 120LM
- Material: ABS
- Switch: 2pcs switch
- Size: 60 x 45 x 35mm Weight: 70g
- IP rating: IP44
- Includes SAA adapter and 1m USB cable in black
- Battery: 1pc polymer 1200Mah lithium battery included
- Work time: approx. 4hrs on full function 100% strong light
- Function: (1) 100% white light (2) 50% white light (3) red light (4) red light flash
- 1 year replacement warranty



LED WORK LIGHTS & TORCHES

LED65WKL

- Rechargeable 6+5 LED angle work light & torch
- Re-chargeable Lithium battery, 3.7V 2200mAh
- 0.3W LED + 6x0.5W SMD LED, equivalent to approx. 300lm
- Ambient temp: -5 to 45°C
- Working time after: approx. 5hrs
- The ambient temp will affect the time of charging and discharging
- AC adaptor: 100-240V input, 5V 1000mA output
- Strong magnetic, adjustable angle work light
- 1 year replacement warranty



LED41WKL

- Rechargeable 4+1 LED angle work light & torch
- Re-chargeable Lithium battery
- Will run for approx. 3 hours after a full charge
- Charging time approx. 5.5 hours
- 1 year replacement warranty



LED WORK LIGHTS



TOE25PRO

- Cordless rechargeable
- 60pcs MCD LED chips
- Colour temp: 6400K, lumens: 380lm
- Length: 380mm
- Life time of LED: 50,000hrs
- 5hrs use and 5hrs charge time
- Water, oil and shock resistant IP54
- Switch on handle, swivel hanging hook
- 240V charger included
- Australian Standards Approved
- Carton QTY: 1/10
- 1 year replacement warranty



TOE2530PRO

- Cordless rechargeable
- 30pcs MCD LED chips
- Colour temp: 6400K, lumens: 200lm
- Length: 350mm
- Life time of LED: 50,000hrs
- 5hrs use and 5hrs charge time
- Water, oil and shock resistant IP54
- Switch on handle, swivel hanging hook
- 240V charger included
- Australian Standards Approved
- Carton QTY: 1/10
- 1 year replacement warranty



EX-288

- LED multi voltage 288pcs LED chips tube light
- Wattage: 20W
- 1500 lumens watt efficiency
- Low power consumption 1.5Amp current draw 12V DC
- Includes 6.8m double insulated cable with IP65 joiner plug for 12V-24V DC use (complete with cigarette plug socket and battery clamp adaptor) and SAA approved driver for 240V AC use
- Smart boost design allows for full light output even on a less than fully charged battery to 9V
- 1.2m input cable with waterproof IP65 on/off switch
- Adjustable velcro straps and plastic coated hanging hooks
- Suitable for use in workshops, camping, automobile, outdoors
- Carton QTY: 1/20
- 1 year replacement warranty



EX-108

- LED multi voltage 108pcs LED chips tube light
- Wattage: 8W
- 800 lumens of super white light using
- Twice as bright than similar 11W fluorescent power cable
- Austrian Standards Approved wall plug 240V AC driver
- Solid state lighting technology makes for much improved vibration and impact protection over fluorescent work light
- Upgraded plastic coated steel swivel hanging hook with anti-roll handle and 180 degree light beam
- IP rating: IP54 water and oil resistant
- 35,000hrs design life time
- Carton QTY: 1/10
- 1 year replacement warranty



EX-10812V (Cigarette Plug)

- 12 volt cable, 12VDC
- Wattage: 8 watts
- Lumens: 800 lumens
- 108 hi Intensity SMD LEDs
- IP rating: IP54 water and oil resistant
- Switch on handle
- Swivel hanging metal hook
- Metal swivel hook
- Australian/NZ standards approved
- Powerful wide beam
- Cigarette plug with battery adaptor
- 12 month warranty

