



Security Lights

SEC

- Surface mounted LED PAR30 security Lights with / without sensor
- Adjustable: up/down & side to side
- Input voltage: 240V AC
- Housing: PBT + PC
- E27 lamp holder
- Max.150W halogen PAR30 globes
- 10W LED PAR30 globe (Part No. PAR3001) included

Sensor Spec:

- Detection range: 180°
- Detection distance: 5-12m
- Detection motion speed: 0.6-1.5m/s
- Rated load: 1200W (HAL) 300W (CFL & LED)
- Time delay: Min: 10s±3s; Max: 10m±3min
- Ambient light: 3-2000 lux (adj)
- Ambient temp: -10 to 40°C
- Installation height: 1.8-2.5m
- Manual override via light switch



| Part No. | Description | PAR3001 INFO | | | | | | Carton QTY |
|----------|--|--------------|---------|-------|-----|------|------------|------------|
| | | Kelvin | Lumens | Watt | CRI | BEAM | LEDs | |
| SEC01 | SECURITY PAR30 ES S/ADJ BLK without sensor | 5000K | 800lm | 10W | 80 | 40° | 10pcs 2835 | 1/40 |
| SEC01S | SECURITY PAR30 ES S/ADJ BLK with sensor | 5000K | 800lm | 10W | 80 | 40° | 10pcs 2835 | 1/32 |
| SEC02 | SECURITY PAR30 X 2 ES D/ADJ BLK without sensor | 5000K | 2x800lm | 2x10W | 80 | 40° | 10pcs 2835 | 1/24 |
| SEC02S | SECURITY PAR30 X 2 ES D/ADJ BLK with sensor | 5000K | 2x800lm | 2x10W | 80 | 40° | 10pcs 2835 | 1/24 |

LED Globes Other Spec (Part No. PAR3001):

- LED chips: 10pcs SMD2835
- Power factor: ≥0.5
- Ambient temp: -10 to 40°C
- Suitable for 2-way switching
- Suitable for use with PIR sensor

